



**ACADIAN INDUSTRIAL TEXTILES  
GROUND COVER FABRIC  
STANDARD L  
STYLE 19284-S**

Specifications

<b>FIBER CONTENT</b>	100% Polypropylene
<b>CONSTRUCTION</b>	22 x 10.5
<b>WEIGHT ASTM D-5261</b>	3.0 oz/sq.yd.
<b>TENSILE STRENGTH ASTM D-4632, Grab Method</b>	Warp: 175 lbs. Fill: 115 lbs.
<b>ELONGATION ASTM D-4632, Grab Method</b>	Warp: 24% Fill: 20%
<b>BURST STRENGTH ASTM D-3786</b>	315 lbs/sq.in.
<b>PUNCTURE STRENGTH ASTM D-4833</b>	76 lbs
<b>TEAR STRENGTH ASTM D-4533, Trap Method</b>	Warp: 75 lbs. Fill: 60 lbs.
<b>WATER FLOW RATE ASTM D-4491</b>	6 gal/sq.ft./min
<b>UV RESISTANCE, STRENGTH RETAINED</b>	70% at 2,500 hrs
<b>UV INHIBITOR</b>	Minimum 2% Carbon Black

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.